

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP240NUP2..-EZylinderrollenlager

## Cylindrical roller bearings

### NUP240-E-M1 (Series NUP2..-E)

main dimensions to DIN 5412-1, locating bearing,  
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	200 mm
D	360 mm
B	58 mm
B <sub>3</sub>	9 mm
D <sub>1</sub>	311,5 mm
d <sub>1</sub>	257,6 mm
D <sub>a</sub> max	343 mm
d <sub>a</sub> min	217 mm
d <sub>c</sub> min	261 mm
E	323 mm
F	243 mm
r <sub>1</sub> min	4 mm
r <sub>a</sub> max	3 mm
r <sub>min</sub>	4 mm
m	28 kg Mass
C <sub>r</sub>	750000 N Basic dynamic load rating, radial
C <sub>0r</sub>	1040000 N Basic static load rating, radial
C <sub>ur</sub>	121000 N Fatigue limit load, radial
n <sub>G</sub>	2900 1/min Limiting speed

nb

1600 1/min Reference speed



