

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP2234NUP22..-EZylinderrollenlager

Cylindrical roller bearings

NUP2234-E-XL-M1 (Series NUP22..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	170 mm
D	310 mm
B	86 mm
B ₃	12 mm
D ₁	269,9 mm
d ₁	219 mm
D _a max	293 mm
d _a min	187 mm
d _c min	223 mm
E	281 mm
F	205 mm
r ₁ min	4 mm
r _a max	3 mm
r _{min}	4 mm
m	30,2 kg Mass
C _r	1130000 N Basic dynamic load rating, radial
C _{0r}	1400000 N Basic static load rating, radial

Cur	212000 N	Fatigue limit load, radial
nc	3300 1/min	Limiting speed
nb	1470 1/min	Reference speed



