

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP2232NUP22..-EZylinderrollenlager

Cylindrical roller bearings

NUP2232-E-XL-M1 (Series NUP22..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	160 mm
D	290 mm
B	80 mm
B ₃	12,5 mm
D ₁	251,1 mm
d ₁	205,5 mm
D _a max	276 mm
d _a min	174 mm
d _c min	210 mm
E	261 mm
F	193 mm
r ₁ min	3 mm
r _a max	2,5 mm
r _{min}	3 mm
m	24,5 kg Mass
C _r	940000 N Basic dynamic load rating, radial
C _{0r}	1170000 N Basic static load rating, radial

Cur	183000 N	Fatigue limit load, radial
nc	3600 1/min	Limiting speed
nb	1660 1/min	Reference speed



