

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP206NUP2..-EZylinderrollenlager

Cylindrical roller bearings

NUP206-E-XL-TVP2 (Series NUP2..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm
D	62 mm
B	16 mm
B ₃	3 mm
D ₁	52,5 mm
d ₁	41,1 mm
D _a max	56 mm
d _a min	34 mm
d _c min	44 mm
E	55,5 mm
F	37,5 mm
r ₁ min	0,6 mm
r _a max	1 mm
r _{min}	1 mm
m	0,219 kg Mass
C _r	46000 N Basic dynamic load rating, radial
C _{0r}	37500 N Basic static load rating, radial

Cur	5400 N	Fatigue limit load, radial
nc	14200 1/min	Limiting speed
nb	9600 1/min	Reference speed



