

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP222-NUP2..-EZylinderrollenlager

Cylindrical roller bearings

NUP222-E-XL-TVP2 (Series NUP2..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	110 mm
D	200 mm
B	38 mm
B ₃	6 mm
D ₁	173,8 mm
d ₁	141,6 mm
D _a max	188 mm
d _a min	122 mm
d _c min	144 mm
E	180,5 mm
F	132,5 mm
r ₁ min	2,1 mm
r _a max	2,1 mm
r _{min}	2,1 mm
m	5,02 kg Mass
C _r	345000 N Basic dynamic load rating, radial
C _{0r}	365000 N Basic static load rating, radial

Cur	59000 N	Fatigue limit load, radial
nc	4100 1/min	Limiting speed
nb	3250 1/min	Reference speed



