

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP2226NUP22..-EZylinderrollenlager

# Cylindrical roller bearings

## NUP2226-E-XL-TVP2 (Series NUP22..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	130 mm
D	230 mm
B	64 mm
B <sub>3</sub>	10 mm
D <sub>1</sub>	201,2 mm
d <sub>1</sub>	164 mm
D <sub>a</sub> max	216 mm
d <sub>a</sub> min	144 mm
d <sub>c</sub> min	168 mm
E	209,5 mm
F	153,5 mm
r <sub>1</sub> min	3 mm
r <sub>a</sub> max	2,5 mm
r <sub>min</sub>	3 mm
m	10,8 kg Mass
C <sub>r</sub>	620000 N Basic dynamic load rating, radial
C <sub>0r</sub>	730000 N Basic static load rating, radial

Cur	118000 N	Fatigue limit load, radial
nc	3500 1/min	Limiting speed
nb	2280 1/min	Reference speed



