

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP217-NUP2..-EZylinderrollenlager

# Cylindrical roller bearings

## NUP217-E-XL-TVP2 (Series NUP2..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	85 mm
D	150 mm
B	28 mm
B <sub>3</sub>	4,5 mm
D <sub>1</sub>	131,5 mm
d <sub>1</sub>	107,5 mm
D <sub>a</sub> max	139 mm
d <sub>a</sub> min	96 mm
d <sub>c</sub> min	110 mm
E	136,5 mm
F	100,5 mm
r <sub>1</sub> min	2 mm
r <sub>a</sub> max	2 mm
r <sub>min</sub>	2 mm
m	2,08 kg Mass
C <sub>r</sub>	194000 N Basic dynamic load rating, radial
C <sub>0r</sub>	194000 N Basic static load rating, radial

Cur	33500 N	Fatigue limit load, radial
nc	5600 1/min	Limiting speed
nb	4000 1/min	Reference speed



