

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP224-ENUP2..-EZylinderrollenlager

Cylindrical roller bearings

NUP224-E-XL-TVP2 (Series NUP2..-E)

main dimensions to DIN 5412-1, locating bearing,
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	120 mm
D	215 mm
B	40 mm
B ₃	6 mm
D ₁	187,8 mm
d ₁	153,2 mm
D _a max	203 mm
d _a min	132 mm
d _c min	156 mm
E	195,5 mm
F	143,5 mm
r ₁ min	2,1 mm
r _a max	2,1 mm
r _{min}	2,1 mm
m	6,02 kg Mass
C _r	390000 N Basic dynamic load rating, radial
C _{0r}	415000 N Basic static load rating, radial

Cur	68000 N	Fatigue limit load, radial
nc	3750 1/min	Limiting speed
nb	3050 1/min	Reference speed



