

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP215-NUP2..-EZylinderrollenlager

Cylindrical roller bearings

NUP215-E-XL-TVP2 (Series NUP2..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	75 mm
D	130 mm
B	25 mm
B ₃	4 mm
D ₁	114,4 mm
d ₁	94,4 mm
D _a max	121 mm
d _a min	84 mm
d _c min	96 mm
E	118,5 mm
F	88,5 mm
r ₁ min	1,5 mm
r _a max	1,5 mm
r _{min}	1,5 mm
m	1,33 kg Mass
C _r	155000 N Basic dynamic load rating, radial
C _{0r}	157000 N Basic static load rating, radial

Cur	27500 N	Fatigue limit load, radial
nc	6500 1/min	Limiting speed
nb	4400 1/min	Reference speed



