

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NU2206-ENU22...EZylinderrollenlager

Cylindrical roller bearings

NU2206-E-XL-TVP2 (Series NU22...-E)

main dimensions to DIN 5412-1, non-locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

(https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm
D	62 mm
B	20 mm
D ₁	52,5 mm
D _a max	56 mm
d _a max	37 mm
d _a min	34 mm
d _b min	40 mm
E	55,5 mm
F	37,5 mm
r ₁ min	0,6 mm
r _{a1} max	0,6 mm
r _a max	1 mm
r _{min}	1 mm
s	1,6 mm Axial displacement facility from central position

m	0,255 kg	Mass
Cr	58000 N	Basic dynamic load rating, radial
Cor	50000 N	Basic static load rating, radial
Cur	7800 N	Fatigue limit load, radial
nG	14200 1/min	Limiting speed
nB	8000 1/min	Reference speed



