


## Data sheet for three-phase Squirrel-Cage-Motors



**Ordering data :** 1LA7134-6AA11

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Electrical data:

Rated motor voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	5.50 kW		6.30 kW			
Rated motor speed :	950 1/ min		1150 1/ min			
Rated motor torque :	55.3 Nm		52.3 Nm			
Rated motor current (IE) :	VD	VY	VY			
	21.91 A	12.60 A	12.20 A			
Starting / rated motor current :	5.0		5.4			
Breakdown / rated motor	2.6		2.6			
Starting / rated motor torque :	2.3		2.3			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	83.1%	83.1%	82.1%	85.0%	85.0%	84.0%
Power factor :	0.76	0.70	0.58	0.76	0.70	0.58
Efficiency class :	-/-		IE1			

### Mechanical data:

Sound pressure level 50 Hz/60Hz (load) :	63 dB(A)	70 dB(A)
Moment of inertia :	0.025 kg*m <sup>2</sup>	
Bearing DE :	6208 2ZC3	
Bearing NDE :	6208 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

### Explosion protection:

Type of protection : without (standard)

### Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

### General data:

Frame size	132 M
Type of construction :	(1) IM B5 / V1 without canopy
Weight in kg, without optional accessories :	52.00 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

### Terminal box:

Material of terminal box :	Aluminum
Type of terminal box :	gk 230
Contact screw thread :	M4
Max. cross-sectional area :	6.00 mm <sup>2</sup>
Cable diameter from ... to ... :	11.00 mm - 21.00 mm
Cable entry :	
Cable gland :	

### Special design: