

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP33NUP3..-EZylinderrollenlager

Cylindrical roller bearings

NUP330-E-XL-M1 (Series NUP3..-E)

main dimensions to DIN 5412-1, locating bearing,
separable, with cage



The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

(https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

| | |
|-----------------------|--|
| d | 150 mm |
| D | 320 mm |
| B | 65 mm |
| B ₃ | 10 mm |
| D ₁ | 269,8 mm |
| d ₁ | 209,5 mm |
| D _a max | 303 mm |
| d _a min | 167 mm |
| d _c min | 213 mm |
| E | 283 mm |
| F | 193 mm |
| r ₁ min | 4 mm |
| r _a max | 3 mm |
| r _{min} | 4 mm |
| m | 27,8 kg Mass |
| C _r | 900000 N Basic dynamic load rating, radial |
| C _{0r} | 930000 N Basic static load rating, radial |
| C _{ur} | 138000 N Fatigue limit load, radial |
| n _G | 3200 1/min Limiting speed |

nb

1940 1/min Reference speed



