

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NU232-E-XLNU2..-EZylinderrollenlager

Cylindrical roller bearings

NU232-E-XL-M1 (Series NU2..-E)

main dimensions to DIN 5412-1, non-locating bearing,
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

(https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	160 mm
D	290 mm
B	48 mm
D ₁	249,6 mm
D _a max	276 mm
d _a max	192 mm
d _a min	174 mm
d _b min	197 mm
E	259 mm
F	195 mm
r ₁ min	3 mm
r _{a1} max	2,5 mm
r _a max	2,5 mm
r _{min}	3 mm
s	4,1 mm Axial displacement facility from central position
m	14,7 kg Mass
C _r	590000 N Basic dynamic load rating, radial

C_{0r}	670000 N	Basic static load rating, radial
C_{ur}	79000 N	Fatigue limit load, radial
n_G	3650 1/min	Limiting speed
n_B	2160 1/min	Reference speed



